

## Conventional Memory

Windows 95 loads its own 32-bit drivers for most hardware (i.e. CD-ROM), so you do not need to load a DOS 16-bit TSR. I would recommend making the following changes to your AUTOEXEC.BAT and CONFIG.SYS files. If there are any lines in these files other than those listed below, type **rem** followed by a space in front of each line to tell the computer to ignore them. (If there are problems with a specific program, you can come back and remove the **rem** from a particular line.) To edit your AUTOEXEC.BAT and CONFIG.SYS:

1. Go to Start, Run.
2. Type **sysedit** and press [Enter] to open your System Configuration Editor.
3. The top window is your AUTOEXEC.BAT file; make the changes below and choose File, Save.
4. You can now select the CONFIG.SYS file by clicking on the blue bar with its name.
5. Make the changes below and choose File, Save.
6. When you have finished, close the System Configuration Editor and then Shutdown your computer and reboot.

### AUTOEXEC.BAT

```
path c:\; c:\datacad
set dc-mouse=4
set dcad_root=c:\datacad
```

(Where datacad is your  
DataCAD directory.)

### CONFIG.SYS

```
device=c:\windows\himem.sys
device=c:\windows\emm386.exe ram
dos=high,umb
files=40
buffers=15
```